

# INDOOR DIGITAL SIGNAGE

## LARGE SIZE FORMAT APPLIED SCREEN

CLASS	MODEL
46"	D46EM

### KEY FEATURES

- Special DOOH LED BLU LCD Panel
- LED BLU, Slim Design
- Power Consumption Reduced at 40% Compared to Normal Display
- Built in Video Wall Function
- Portrait / Landscape Orientation
- High Connectivity
- Remote Control (RS232)



## Broadcast your branding with Hyundai Digital Signage!

Thanks to the advanced product design, Hyundai Digital Signage Display meets requirements for various digital signage solutions. Not only take advantage from slim and simple design, but also think more about our future environment, saving energy up to 40 percent. LED technologies bring more than just expected.



**SPECIFICATIONS**

Model	D46EM	
Panel	Screen Size (diagonal)	46"
	Active Display Area (inch / mm)	40.08 x 22.55 / 1018.08 x 572.67
	Resolution	1920 x 1080
	Aspect Ratio	16:9
	Display Colors	1.07B
	Brightness (cd/m <sup>2</sup> ; typ.)	500
	Contrast Ratio	4000:1
	Response Time (ms; GTG)	6.5
	Viewing Angle	178°/178°
	Lifetime (hours)	50,000
	Backlight type	LED
	Resolution	Monitor
DTV		1080p
Input	1 x DP(Optional)   1 x HDMI   1 x DVI   1 x VGA(D-Sub)   1x IR   1x RS232C	
Output	1x DVI   1x IR   1x RS232C   Audio Line Out   Speaker (Ready)	
Power	Input Voltage	100 – 240V AC
	Power consumption	110 W
Features	PIR Sensor (Motion detection)	Option
	Auto Power Control	Yes
	Auto Brightness Sensor	Yes
Operation	Temperature (°C)	0 - 40
	Humidity (%)	20 - 80
	OSD Language	10 Lang
Dimension	Set (W x H x D), in   mm	41.3 x 23.67 x 1.59   1049.1 x 601.25 x 40.3
Bezel Size (U/D/L/R), in   mm	0.5 / 0.5 / 0.547 / 0.547   12.7 / 12.7 / 13.9 / 13.9	
Wall Mounting (WxH) mm	300 x 300 / 400 x 400 / 600 x 400 (M6)	
Weight	Set (lb   kg)	44.09   20

**FEATURES**
**Special Out-Of-Home LCD Panel**

By using commercial grade LCD panels for Out-Of-Home applications, HYUNDAI Digital Signage display can provide higher brightness and contrast than standard LCD TV panels. This guarantees longer working time, deliver clear and bright image contents in the portrait or landscape format without any loss of quality.

**LED Backlight**

HYUNDAI's public displays with LED backlight bring the advantage of up to 40% lower power consumption, compared to displays with CCFL backlight.

**Easy operating OSD menu, Remote control**

In order to setup a multi display wall, the single units are linked by a daisy chain connection over DVI interface. The configuration of each display can be easily set-up over the on-screen menu or the RS232C interface.

**Slim Design**

These products enable the slim design.

**DIMENSIONS**

[Unit: inch / mm]

